







TURCK works Industrial Automation

3, 4 and 5-Wire Cordsets, "A" Style Extreme Duty Armored Plug Body - 18 AWG

- **Shield to Coupling Nut**
- **NEMA 1, 3, 4, 6P and IEC IP68 Protection**
- **250 V, 4 A**



Connector Style	Female Part Number	Male Part Number	Features	Pinout	
RKA .. 	RKA 4A-*	RSA 4A-*	Interlock Al Armor, MC/ITC/PLTC, PVC Yellow, 3x18 AWG, 105°C, 13.5 mm OD, Cable #RF51040-*M†, Extreme Duty Armored Cable, Tray Rated	1. BK 2. N/C 3. WH 4. GN	Female  Male 
	RKA 4.4A-*	RSA 4.4A-*	Interlock Al Armor, MC/ITC/PLTC, PVC Yellow, 4x18 AWG, 105°C, 13.5 mm OD, Cable #RF51041-*M†, Extreme Duty Armored Cable, Tray Rated	1. BK 2. WH 3. RD 4. GN	Female  Male 
RSA .. 	RKA 4.5A-*	RSA 4.5A-*	Interlock Al Armor, MC PVC Yellow, 5x18 AWG, 90°C, 14.9 mm OD, Cable #RF51042-*M†, Extreme Duty Armored Cable	1. BK 2. WH 3. RD 4. GN 5. OG	Female  Male 

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.
** Standard coupling nut material is nickel plated brass "RKA .."; "RKAV .." indicates stainless steel.
† See Section N for ***reelfast***® cable information.