

3 and 4-Wire Cordsets, "G" Style Large Plug Body

- NEMA 1, 3, 4, 6P
- IEC IP68 Protection
- 250 V, 4 A



Connector Style	Female Part Number	Male Part Number	Features	Pinout
 	RKG 4T-*	RSG 4T-*	ITC/PLTC PVC Yellow, 3x18 AWG, 105°C, 7.2 mm OD, Cable #RF50513-*M [†] , flexlife [°] , tray rated	1. BN 2. N/C 3. BU 4. BK
	RKG 4T-*/S600	RSG 4T-*/S600	SJOOW, CPE Yellow, 3x18 AWG, 105°C, 8.0 mm OD, Cable #RF50654-*M [†] , Weld Flash Immune, Flame Resistance	
	RKG 4.4T-*	RSG 4.4T-*	AWM PVC Yellow, 4x18 AWG, 105°C, 7.2 mm OD, Cable #RF50579-*M [†] , flexlife	
	RKG 4.4T-*/S90	RSG 4.4T-*/S90	ITC/PLTC TPU Yellow, 4x18 AWG, 90°C, 7.2 mm OD, Cable #RF50544-*M [†] , Cut/Abrasion Immune	
	RKG 4.4T-*/S101/S849	RSG 4.4T-*/S101/S849	AWM TPE Grey, 4x22 AWG, 105°C, 5.7 mm OD, Cable #RF50941-*M [†] , flexlife-20, High Flex - Over 20 Million Cycles	
	RKG 4.4T-*/S101	RSG 4.4T-*/S101	AWM TPE Yellow, 4x18 AWG, 105°C, 6.4 mm OD, Cable #RF50968-*M [†] , flexlife-20, High Flex - Over 20 Million Cycles	
	RKG 4.4T-*/S529	RSG 4.4T-*/S529	TPU/Heavy Braid Double Jacket Yellow, 4x20 AWG, 90°C, 5.7 mm OD, Cable #RF50526-*M [†] , Cut/Abrasion Immune, Braided Mechanical Shield	
	RKG 4.4T-*/S1587	RSG 4.4T-*/S1587	ITC/PLTC TPE Yellow, 4x18 AWG, 105°C, 7.2 mm OD, Cable #RF50956-*M [†] , weldlife, Weld Flash Immune	

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.

** Standard coupling nut material is nickel plated brass "RKG .."; "RKG .." indicates stainless steel.

† See Section N for **reelfast**® cable information.