

9, 10 and 12-Wire Receptacles, Front Mount

- NEMA 1, 3, 4, 6P
- IEC IP68 Protection
- 600 V, 7 A



Housing Style	Female Part Number	Male Part Number	Features	Pinout
RKF ...1/2-14NPT Typical panel cutout 22.5 mm	RKF 96-*M/14.5/NPT	RSF 96-*M/14.5/NPT	9x16 AWG, 105°C, 1/2-14 NPT threads	Female Male
RSF ..1/2-14NPT Typical panel cutout is 22.5 mm	RKF 106-*M/14.5/NPT	RSF 106-*M/14.5/NPT	10x16 AWG, 105°C, 1/2-14 NPT threads	Female Male
RSF ..1/2-14NPT Typical panel cutout is 22.5 mm	RKF 126-*M/14.5/NPT	RSF 126-*M/14.5/NPT	12x16 AWG, 105°C, 1/2-14 NPT threads	Female Male

Standard lead length is 0.3 Meters. Consult factory for other lengths.

** Standard housing material is nickel plated brass.. "RSF .."; "RSFV .." indicates stainless steel housing.

For locknuts to be included, add "W/LN" to the end of the part number.

To specify PVC jacketed cable, add "/S717" to the end of the part number.