

3, 4, 5 and 6-Wire Washdown Cordsets

- NEMA 1, 3, 4, 6P
- IEC IP68 Protection
- Polypropylene Contact Holder, Mold Material and Cable Jacket
- High chemical solvent resistance, high tensile strength



Connector Style	Female Part Number	Male Part Number	Features	Pinout
WD-RKCV.. WD-WKCV.. WD-RSCV.. WD-WSCV..	WD-RKCV 4T-* WD-WKCV 4T-*	WD-RSCV 4T-* WD-WSCV 4T-*	PP White, 3x20 AWG 105°C, 250 V, 4 A 5.1 mm OD, Cable #RF51440-*M	Female Male
	WD-RKCV 4.4T-* WD-WKCV 4.4T-*	WD-RSCV 4.4T-* WD-WSCV 4.4T-*	PP White, 4x22 AWG 105°C, 250 V, 4 A 4.4 mm OD, Cable #RF51359-*M	Female Male
	WD-RKCV 4.5T-* WD-WKCV 4.5T-*	WD-RSCV 4.5T-* WD-WSCV 4.5T-*	PP White, 5x22 AWG 105°C, 250 V, 4 A 4.5 mm OD Cable #RF51466-*M	Female Male
	WD-RKCV 6T-* WD-WKCV 6T-*	WD-RSCV 6T-* WD-WSCV 6T-*	PP White, 6x24 AWG 105°C, 60 VAC/75 VDC, 2 A 4.5 mm OD Cable #RF51467-*M	Female Male

* Length in meters. Standard cable lengths are 2, 4, 5, 6, 8 and 10 meters. Consult factory for other lengths.
Standard coupling nut material is stainless steel.