

## minifast® lokfast™ Guards

- Straight and Right Angle **minifast** Style Connectors
- Nylon



Part Number	Application
LOCK-MINI	Locking guard for straight <b>minifast</b> standard body connectors (RKM, RKV, RSM and RSV) in Class I, Division 2 installations*
LOCK-MINI (10/BAG)	
LOCK-MINI-ANGLE	Locking guard for right angle <b>minifast</b> standard body connectors (WKM, WKV, WSM and WSV) in Class I, Division 2 installations*
LOCK-MINI-ANGLE (10/BAG)	
LOCK-MINI-FW	Locking guard for straight <b>minifast</b> field wireable connectors (BS 41... and B 41...) in Class I, Division 2 installations*
LOCK-MINI-FW (10/BAG)	
LOCK-MINI-B&C	Locking guard for straight <b>minifast "B" Style</b> and <b>"C" Style</b> connectors (RKM, RKV, RSM and RSV) in Class I, Division 2 installations*
LOCK-MINI-B&C (10/BAG)	
LOCK-MINI-B&C-ANGLE	Locking guard for right angle <b>minifast "B" Style</b> and <b>"C" Style</b> connectors (WKM, WKV, WSM and WSV) in Class I, Division 2 installations*
LOCK-MINI-B&C-ANGLE (10/BAG)	

\* See **TURCK** Control Drawing QCF-00147 ([www.turck.com/fmcd/](http://www.turck.com/fmcd/)) for guidance on installation in hazardous locations.



*lokfast Open*

*lokfast Closed*