

- NEMA 1, 3, 4, 6P
- IEC IP67 Protection



Housing Style	Female Part Number	Male Part Number	Features	Pinout	
RKF .. Typical panel cutout 22.5 mm	RKF 20-*M	RSF 20-*M	2x18 AWG 105°C, 600 V, 9 A, standard duty	1. BN 2. BU	Male/Female Male/Female
	RKF 26-*M	RSF 26-*M	2x16 AWG Leads, 105°C, 600 V, 10 A, heavy duty	1. WH 2. BK	
	RKF 28-*M	RSF 28-*M	2x18 AWG, 105°C, 600 V, 9 A, heavy duty	1. WH 2. BK	
	RKF 30-*M	RSF 30-*M	3x18 AWG, 105°C, 600 V, 9 A, standard duty	1. GY/YE 2. BN 3. BU	Female Female
RKF 31-*M	RSF 31-*M	3x18 AWG, 105°C, 600 V, 9 A, standard duty	1. BK 2. BN 3. BU		
	RSF 31-*M/S849	3x22 AWG, 105°C, 300 V, 5 A, standard duty			
RKF 311-*M	RSF 311-*M	3x18 AWG, 105°C, 600 V, 9 A, automotive color code			
	RSF 311-*M/S849	3x22 AWG, 105°C, 300 V, 5 A, automotive color code	1. GN 2. RD/BK 3. RD/WH		
RKF 35-*M	RSF 35-*M	3x16 AWG, 105°C, 600 V, 10 A, automotive color code			
RKF 36-*M	RSF 36-*M	3x16 AWG, 105°C, 600 V, 10 A, heavy duty	1. GN 2. BK 3. WH		
	RKF 38-*M	RSF 38-*M	3x18 AWG, 105°C, 600 V, 9 A, heavy duty	1. GN 2. BK 3. WH	

Standard lead length is 0.3 Meters. Consult factory for other lengths.

** Standard housing material is nickel plated brass.. "RSF .."; "RSFV .." indicates stainless steel housing, and "RSFK .." indicates nylon housing.

For locknuts to be included, add "W/LN" to the end of the part number.

To specify PVC jacketed cable, add "/S717" to the end of the part number.