

## A-Series Miniature Watertight Pressure Switches

### FEATURES

- Compact size
- 316 SS construction
- Pressure ranges from vacuum to 15,000 psi
- Factory set or field adjustable setpoints
- Wide operating temperature range (-40°C to 100°C)
- Precision snap-acting micro switch
- SPDT or DPDT switching
- UL, CSA listed models
- CE and ROHS compliant
- CRN models available (up to 10,000 psi)
- SIL 3 capable

### TYPICAL USES

- Offshore oil rigs
- Chemical and petrochemical plants
- Pulp and papermills
- Autoclaves and sterilizers
- Rail and heavy vehicles
- Specialty machinery and equipment



**A-Series**  
Watertight Pressure Switch



### SPECIFICATIONS

Setpoint:	Single setpoint - Factory set or field adjustable
Setpoint Repeatability:	±2% of span. For ranges 200 through 15,000 psi ±5% of span. For ranges -15/15 through 100 psi (additional setpoint shift ±2% of span per 40°F from initial setpoint setpoint at 70°F typical)
Vibration:	Passed Mil-STD-202G
Shock:	75G's 10 milliseconds 3 axis
Piston:	SS w/Viton or Buna-N O-ring
Mechanical life piston design:	>1,000,000 operations typical
Diaphragm:	316L SS
Mechanical life diaphragm design:	>400,000 operations typical
Switch Type:	SPDT or DPDT
Deadband:	Fixed
Enclosure Ratings:	NEMA 6, IP67
Enclosure material:	316L SS
Pressure Connection:	1/8 NPTF, 1/4 NPTF, 1/4 NPTM, 1/8 NPTM, 1/2 MNPT, 1/2 FNPT, 7/16-20 SAE M, VCR, VCO, 3/4" Tri-Clamp®, 1.5" Tri-Clover®, 2.0" Tri-Clover, G1/4 B, G1/4 A Type E Stub end
Electrical output:	SPDT, or DPDT 5A or 3A 120Vac, 2A @ 30Vdc, gold contacts available
Approvals:	UL, CSA, CE, CRN, SIL 3 capable, RoHS

### KEY BENEFITS

- High performance
- Small size
- Special connections
- Easily configurable to meet your application requirements
- SIL 3 capable

## A-Series Miniature Watertight Pressure Switches

### CHARACTERISTICS AND RATINGS

A SERIES SWITCH PERFORMANCE CHARACTERISTICS												
RANGE (Ordering Code)			SETPOINT REPEATABILITY			SETPOINT ADJUSTABILITY			DEADBAND (DB)			
DIAPHRAGM	psi (#)	bar, kg/cm <sup>2</sup> (BAR) (KSC)	kPa (KP)	psi	bar, kg/cm <sup>2</sup>	kPa	psi	bar, kg/cm <sup>2</sup>	kPa	psi	bar, kg/cm <sup>2</sup>	kPa
DIAPHRAGM	-15/15	-1/1	-100/100	±1.5	±.10	±10	-15/15	-1/1	-100/100	1-5	0.07-.35	7-35
	30	2	200	±1.5	±.10	±10	6-30	0.4-2	6-200	1-5	0.07-.35	7-35
	60	4	400	±3.0	±.21	±21	8-60	0.6-4	60-400	2-10	0.14-.70	14-70
	100	7	700	±5.0	±.34	±34	10-100	0.7-7	70-700	3-15	0.2-1.0	20-100
	200	14	1400	±4	±0.28	±28	20-200	1.4-14	140-1,400	3-30	0.2-2.0	20-200
PISTON	100	7	700	±5.0	±.34	±34	20-100	1.4-7	140-700	3-15	0.2-1.0	20-100
	200	14	400	±4	±.28	±34	40-200	2.8-14	280-1,400	3-30	0.2-2.0	20-200
	500	35	3500	±10	±.70	±70	50-500	3.5-35	350-3,500	20-100	1.4-7.0	140-700
	1000	70	7000	±20	±1.40	±140	100-1,000	7-70	700-7,000	25-150	1.7-10	170-1,000
	2000	140	14000	±40	±2.8	±280	200-2,000	14-140	1,400-14,000	30-300	2-20	200-2,000
	5000	350	35000	±100	±7.0	±700	500-5,000	35-350	3,500-35,000	75-750	5-50	50-5,000
	7500	500	50000	±150	±10	±1,000	750-7,500	50-500	5,000-50,000	110-1,100	7.5-75	750-7,500
	10000	700	70000	±200	±14.0	±1,400	100-10,000	70-700	7,000-70,000	250-2,500	17-170	1,700-1,700
	15000	1000	100000	±300	±20	±2,000	1,500-15,000	100-1,000	10,000-100,000	300-3,000	20-200	200-20,000

OPTIONS		Description	
Code	C4	Individual certified calibration chart	
	FP	Fungus proofing	
	MQ	Positive Material Identification (75, 15 & 20 process conn. only)	
	NC	2 wire leads w/ground wire – wired for normally closed operation	
	NO	2 wire leads w/ground wire – wired for normally open operation	
	NH	SS tag	
	NN	Paper tag	
	6B	Cleaned for oxygen service	
	GO	No ground wire	

MATERIAL AND TEMPERATURE RATINGS (based on mat'l and switch code)		
ACTUATOR SEAL	MATERIAL	TEMPERATURE RANGE
S	316 SS	-40°F to 212°F (-40°C to 100°C)
B (Ranges 100#, 200#)	316 SS, Buna-N®	-4°F to 212°F (-20°C to 100°C)
B (Ranges 500# to 15,000#)	316 SS, Buna-N®	-40°F to 212°F (-40°C to 100°C)
V	316 SS, Viton®	-4°F to 212°F (-20°C to 100°C)
N	316 SS, HNBR	-4°F to 212°F (-20°C to 100°C)

PRESSURE RATINGS												
CONFIGURATION		MAX. WORKING PRESSURE "MWP"			PROOF PRESSURE "PROOF"			BURST PRESSURE				
RANGES (psi)	w/SEAL	psi	bar, kg/cm <sup>2</sup>	kPa	psi	bar, kg/cm <sup>2</sup>	kPa	psi	bar, kg/cm <sup>2</sup>	kPa		
up to 200	S	800	55	5,500	1,000	70	7,000	>9,500	>655	>65,500		
100-200	B, V or N	2,000	140	14,000	2,000	140	14,000	>10,000	>700	>70,000		
500-2,000	B, V or N	5,000	350	35,000	8,000	550	55,000	>30,000	>2,100	>210,000		
5,000-7,500	B, V or N	10,000	700	70,000	15,000	1,000	100,000	>50,000	>3,500	>350,000		
10,000-15,000	B, V or N	15,000	1,000	100,000	20,000	1,400	140,000	>45,000	>31,000	>310,000		




## A-Series Miniature Watertight Pressure Switches

ORDERING CODE		Example:	APS	N4	1	H	012C	S	02	30#	15	R	X6B
<b>Function</b>													
APS - Pressure switch, single setpoint, fixed deadband, factory set, not field adjustable			APS										
APA - Pressure switch, single setpoint, fixed deadband, factory set, field adjustable													
<b>Enclosure</b>													
N4 - Watertight 316 SS body				N4									
<b>Micro Switch, First Character</b>													
1 - Single switch, SPDT					1								
2 - Dual switch - DPDT (N4 - not available with "S" actuator < 100 psi, range, N7 - not available with "S" actuator or P&G micro switch)													
<b>Micro Switch, Second Character</b>													
G - Gold contact - 0.1A @ 125 Vac, 0.1A @ 30 Vdc													
H - High current - 5A @ 125/250 Vac, 5A @ 28 Vdc resistive, 3A @ 28 Vdc inductive						H							
L - High current, gold contact - 1A @ 125 Vac, 1A @ 28 Vdc resistive, 0.5A @ 28 Vdc inductive													
P - General purpose - 3A @ 125 Vac, 2A @ 30 Vdc													
<b>Electrical Connection</b>													
000H - Micro DIN connector - Watertight DIN 43650 Form C cable socket without mating connector, not available with DPDT switching, Not available with N7 enclosure													
00MH - Micro DIN connector - Watertight DIN 43650 Form C cable socket with mating connector, not available with DPDT switching, Not available with N7 enclosure													
000N - Nonstandard, customer specified, see # variation, Not available with N7 enclosure													
000T - Spade Terminals, 4 - 0.187" male spade - not available with DPDT switching, Not available with N7 enclosure													
---C - 1/2 NPT Male conduit with 18 AWG wires (Note ____ e.g. 012C = 12" lead wires, Specify wire length in inches)							012C						
---L - Wire leads, 3-18 AWG PVC insulated wires (Note ____ e.g. 012L = 12" lead wires, Specify wire length in inches), Not available with N7 enclosure													
---G - M20 X 1.5 male conduit connection with 18 AWG wires (Note ____ e.g. 012G = 12" lead wires, Specify wire length in inches)													
---K - M20 X 1.5 male conduit connection with 4 conductor jacketed cable with 18 AWG wires (Note ____ e.g. 012K = 12" lead wires, Specify wire length in inches), not available with DPDT switching, Not available with N7 enclosure													
---J - 1/2 NPT Male conduit connection with 4 conductor jacketed cable with 18 AWG wires (Note ____ e.g. 012J = 12" lead wires, Specify wire length in inches), not available with DPDT switching, Not available with N7 enclosure													
<b>Actuator Seal (see page 6 for more information)</b>													
B - 316 SS piston & Buna-N® O-ring, ranges ≥ 100 psi													
V - 316 SS piston & Viton® O-ring, ranges ≥ 100 psi													
S - 316 SS welded diaphragm, ranges ≤ 200 psi								S					
N - 316 SS piston & HNBR O-ring, ranges ≥ 100 psi													
<b>Process Connection</b>													
01 - 1/8 NPT Male													
02 - 1/4 NPT Male								02					
03 - 1/8 NPT Female (not available for B, V, N actuators)													
04 - 1/2 NPT Male													
05 - 7/16-20 SAE Male													
06 - VCR fixed (not available for B, V, N actuators)													
07 - VCO fixed (not available for B, V, N actuators)													
08 - 7/16-20 SAE Female													
12 - G 1/4 A (Type E Stud End)													
13 - G 1/4 B													
25 - 1/4 NPT Female (not available for B, V, N actuators)													
50 - 1/2 NPT Female													
46 - 7/16-20 SAE Female													
76 - 7/16-20 SAE w/37° flare end													
75 - 3/4 Tri-Clamp® connection (includes 3A approval), range ≤ 1,000 psi													
15 - 1 1/2 Tri-Clamp® connection (includes 3A approval), range ≤ 1,000 psi													
20 - 2.0 Tri-Clamp® connection (includes 3A approval), range ≤ 1,000 psi													
<b>Ranges (See table on page 3 for additional ranges)</b>													
30 psi								30 psi					
<b>Setpoint</b>													
5 Characters maximum representing setpoint of the switch in the same units as the ranges of the switch. For setpoints in vacuum specify as "-" pressure. If no set point is required on an APA switch use either "NSR" or NSD". If direction is not known use "NSR" as default												15	
<b>Setpoint Direction</b>													
R - Rising pressure (increasing pressure, decreasing vacuum)												R	
D - Decreasing pressure (decreasing pressure, increasing vacuum)													
<b>Options - Select from table on page 3 (If choosing an option(s) must include an X")</b>													
6B - Cleaned for oxygen service												X	
												6B	


## A-Series Miniature Watertight Pressure Switches

### DIMENSIONS

For reference only, consult Ashcroft for specific dimensional drawings



**WIRE LEAD (XXXL) CONNECTION  
WITH DUAL SWITCH SHOWN  
XXX = WIRE LENGTH (in.)**



SLIDE COVER DOWN TO ACCESS  
SETPOINT ADJUSTMENT. SLIDE COVER  
UP TO CLOSE AND SEAL ADJUSTMENT

ROTATE LEFT ←  
TO INCREASE SET POINT  
ROTATE RIGHT →  
TO DECREASE SET POINT  
∅.095 OR SMALLER TOOL  
REQUIRED TO ROTATE NUT

FUNCTION CODE	
Description	Dim.A
APS (Factory Set)	1.06
APA (Field Adjustable)	1.64

MICRO SWITCH	
Description	Dim.B
1H, 2H, 1L, 2L	1.03
1P, 1G	0.90

PRESSURE CONNECTION GENERAL DIMENSION			
Code	Description	Dim.C	Dim.D
01	1/8 NPT Male	0.45	0.44
02	1/4 NPT Female	0.56	0.54
03	1/8 NPT Female	0.75	0.65
04	1/2 NPT Male	0.92	0.75
25	1/4 NPT Female	1.10	0.75
50	1/2 NPT Female	1.25	1.04
05	7/16-20 SAE Male	0.56	0.44
08	7/16-20 SAE Female	1.10	0.84
06	VCR Fixed	0.58	0.56
07	VCO Fixed	0.47	0.56
12	G 1/4A	0.47	0.44
13	G 1/4B	0.59	0.37
46	9/16-18 SAE Female	0.39	0.47
76	7/16-20 SAE w/37° Flare End	0.55	0.36
75	3/4" Tri-Clamp Seal	1.10	0.96
15	1 1/2" Tri-Clover Seal	1.23	1.99
20	2.0" Tri-Clover Seal	1.23	2.49



CRN: OF 14836.5C,



CSA: 2454057 (LR55528)



UL: E38812



CE



ROHS

SIL 3 CAPABLE

## A-Series Miniature Watertight Pressure Switches

### AVAILABLE CONNECTIONS

#### Pressure Connections

1/8, 1/4 or 1/2 MALE NPT



1/8 or 1/4 FEMALE NPT,  
7/16-20 SAE FEMALE



VCR or VCO



7/16-20 SAE MALE (OPTIONAL  
37° FLARE END)



3/4", 1.5" or 2.0" SANITARY



G 1/4 A TYPE-E STUD END



1/2 FEMALE NPT



G 1/4 B



#### Electrical Connections

18 AWG WIRE LEADS



1/2 NPT CONDUIT CONNECTOR  
WITH 18 AWG WIRE LEADS



SPADE TERMINAL 4-0.187  
MALE TERMINALS



HIRSCHMANN MICRO-DIN  
CONNECTOR 43650 FORM C



DPDT 18 AWG LEADS



M20 X 1.5 MALE CONDUIT  
WITH 18 AWG WIRES



1/2 NPT MALE CONDUIT AND  
JACKETED CABLE WITH 18  
AWG WIRES



M20 X 1.5 MALE CONDUIT  
AND JACKETED CABLE WITH  
18 AWG WIRES



## A-Series Miniature Watertight Pressure Switches

### SELECTION GUIDE

Before selecting a switch the following should be considered:

#### Actuator:

The actuator responds to changes in pressure and operates the micro switch element in response to these changes. The actuator is normally exposed to the process media and must be chemically compatible with it. There are three types of actuators available for the A-Series switches – all welded 316 SS diaphragm sealed piston; 316 SS piston with Viton O-ring seal; and 316 SS piston with Buna-N O-ring seal. The 316 SS diaphragm is available in ranges from -15/15 psi to 200 psi. The 316 SS piston is available in ranges from 100 psi to 15,000 psi. Switches offered in 100 psi and 200 psi can be ordered with either the piston or diaphragm design. The piston design will have a longer mechanical life, while the diaphragm design has a better operating temperature.

The piston design is more reliable than a diaphragm design when subjected to frequent large pressure excursions, pressure surges and spikes associated with typical hydraulic applications. Piston designs are typically used when the switch is used as low pressure alarm or cutoff where the normal working pressure is above the nominal range of the switch.

#### The Switching Function:

Most applications for alarm, shutdown and interlock are satisfied by the standard A-Series switches which feature single setpoint fixed deadband. For pump, compressor and other control applications, the dead-band becomes a very important consideration and may require increasing the range of the switch to increase the deadband. Please consult your Ashcroft representative for assistance with special applications.

#### The Micro Switch Element:

The micro switch element must be chosen to meet the electrical load requirement to be switched. The switches are offered as either SPDT (single pole double throw) or DPDT (double pole double throw). The DPDT switch is made up of two SPDT switches which are adjusted to work together by Ashcroft's patent pending Circuit Board Rotation Design. DPDT switching is not available on diaphragm designs below 100 psi, with Spade terminals or the Micro DIN connector.


#### Understanding Setpoints and Reset Points:

Pressure switches can be set to switch on either increasing (rising) or decreasing pressures. Since the switches have both Normally Open (NO) contacts and Normally Closed (NC) contacts you can wire the switch to open or close for either an increasing or decreasing pressure. To be consistent in setting the switches Ashcroft defines the setpoints as follows. For an increasing setpoint, the pressure is increased from 0 psi to the set point and then decreased to the reset point. For a decreasing setpoint, the pressure is increased to full range and then decreased to the setpoint and then increased to the reset point.


#### Custom Applications:

The A-series switch is designed to allow custom process connections and electrical terminations. Please consult your Ashcroft representative for assistance with custom applications.

#### Cutaway view of switch assembly with welded SS diaphragm



#### Cutaway view of switch assembly with SS piston



## A-Series Miniature Watertight Pressure Switches

### ADDITIONAL SWITCH TERMINOLOGY

**Accuracy** – (See repeatability) Accuracy normally refers to conformity of an indicated value to an accepted standard value. There is no indication in switch products; thus, instead, the term repeatability is used as the key performance measure.

**Automatic Reset Switch** – Switch which returns to normal state when actuating variable Pressure is reduced.

**Adjustable or Operating Range** – That part of the nominal range over which the switch setpoint may be adjusted. Normally about 10% to 100% of the nominal range for A-Series pressure switches.

**Burst Pressure** – The maximum pressure that may be applied to a pressure switch without causing leakage or rupture. This is approximately 16X of nominal range for A-Series switches. Diaphragm switches subjected to pressures above the nominal range can be permanently damaged.

**Deadband** – The difference between the setpoint and the resetpoint, normally expressed in units of the actuating variable. Sometimes referred to as differential.

**Fixed Deadband** – The difference between the setpoint and the resetpoint of a pressure switch. It further signifies that this deadband is a fixed function of the pressure switch and not adjustable.

#### National Electrical Manufacturers Association (NEMA)

– This group has defined several categories of enclosures, usually referred to as “types.” Further, they designate certain features and capabilities each type must include.

**NEMA 6** – Enclosures constructed for either indoor or outdoor use to provide a degree of protection to personnel against access to hazardous parts; to provide a degree of protection of the equipment inside the enclosure against ingress of solid foreign objects (falling dirt); to provide a degree of protection with respect to harmful effects on the equipment due to the ingress of water (hose directed water and the entry of water during occasional temporary submersion at a limited depth); and that will be undamaged by the external formation of ice on the enclosure.

**Normal Switch Position** – Contact position before actuating pressure (or variable) is applied. Normally closed contacts open when the switch is actuated. Normally open contacts close when the switch is actuated.

**Normally Closed** – Refers to switch contacts that are closed in the normal switch state or position (unactuated). A pressure change opens the contacts.

**Normally Open Switch** – Refers to the contacts that are open in the normal switch state or position (unactuated). A pressure change closes the contacts.

**Overpressure Rating(s)** – A nonspecific term that could refer to either burst or proof pressure, or both.

**Proof Pressure** – The maximum pressure which may be applied without causing damage. This is determined under strict laboratory conditions including controlled rate of change and temperature: This value is for reference only. Consult factory for applications where switch must operate at pressures above nominal range or reference temperature (70°F).

**Repeatability (Accuracy)** – The closeness of agreement among a number of consecutive measurements of the output setpoint for the same value of the input under the same operating conditions, approaching from the same direction, for full-range traverses. *Note:* It is usually measured as non-repeatability and expressed as repeatability in percent of span or nominal range. It does not include hysteresis or deadband.

**Resetpoint** – The resetpoint is the Pressure value where the electrical switch contacts will return to their original or normal position after the switch has activated.

**Setpoint** – The setpoint is the Pressure value at which the electrical circuit of a switch will change state or actuate. It should be specified either on increase or decrease of that variable.

**Single Pole Double Throw (SPDT) Switching Element** – A SPDT switching element has one normally open, one normally closed, and one common terminal. The switch can be wired with the circuit either normally open (N/O) or normally closed (N/C). SPDT is standard with A-series switches.

**Double Pole Double Throw (DPDT) Switching Element** – Two SPDT switching elements both set to actuate or de-actuate at the same set or resetpoint. Each switch one has one normally open, one normally closed, and one common terminal. The switches are independent of each other and can be wired to two independent circuits. The two circuits can either normally open (N/O) or normally closed (N/C).

**Snap Action** – In switch terminology, snap action generally refers to the action of contacts in the switch element. These contacts open and close quickly and snap closed with sufficient pressure to firmly establish an electrical circuit. The term distinguishes products from mercury bottle types that were subject to vibration problems.