Model 1A and 1B

Window Diameter 0.64"

Application:
With ammeters, energy management systems and instrumentation.

Frequency:
50-400Hz

Insulation Level:
600 Volts, 10kV BIL full wave

- Flexible leads are UL 1015 105°C,CSA approved #16 AWG, 24" long.
- Non-standard length to be specified.
- 1 Amp and other secondary currents available upon request.
- Approximate weight:
  Model 1A: 0.42 lb
  Model 1B: 0.59 lb

Approvals


UL 257877

CSA 223647


Catalogue Number	Current Ratio	Accuracy at 60Hz	Burden VA at 60Hz
1A-500	50:5	± 2%	1.0
1A-600	60:5	± 1%	2.0
1A-750	75:5	± 1%	2.0
1A-800	80:5	± 1%	2.0
1A-101	100:5	± 1%	2.5
1A-121	120:5	± 1%	3.0
1A-1250	125:5	± 1%	3.0
1A-151	150:5	± 1%	4.0
1A-201	200:5	± 1%	5.0
1A-251	250:5	± 1%	7.5


Catalogue Number	Current Ratio	Accuracy at 60Hz	Burden VA at 60Hz
1B-500	50:5	± 2%	1.0
1B-600	60:5	± 1%	2.0
1B-750	75:5	± 1%	2.5
1B-800	80:5	± 1%	3.0
1B-101	100:5	± 1%	4.0
1B-121	120:5	± 1%	5.0
1B-1250	125:5	± 1%	5.0
1B-151	150:5	± 1%	7.5
1B-201	200:5	± 1%	10.0
1B-251	250:5	± 1%	12.5





Model 1A







Model 1B

