


# Thermocouples

## Mineral Insulated

### Metal Transitions with Spring Strain Relief Style AF



#### Ordering Information

##### Part Number

①	②	③	④	⑤	⑥	⑦	⑧ ⑨	⑩	⑪	⑫	⑬ ⑭	⑮
Style	Sheath O.D.	Lead Wire Const.	Fittings, Weld Pads	Lead Wire Term.	Sheath Material	Sheath Length "L" (whole in.)	Sheath Length "L" (fract. in.)	Junction	Calibration	Lead Wire Length "E" (whole ft)	Special Rqmts.	
A	F											

##### ② Style

F = Metal transition with strain relief and 300°F (149°C)

##### ③ Sheath O.D. (in.)

B = 0.020  
C = 0.032  
D = 0.040  
E = 0.063  
G = 0.125  
H = 0.188  
J = 0.250

##### ④ Lead Wire Construction

		Standard	Overbraid	Flex Armor
Fiberglass	Solid	A	J	R
FEP	Solid	C	L	T
Fiberglass	Stranded*	B	K	S
FEP	Stranded*	D	M	U

\*Stranded lead wire available only for sheath O.D. 0.063 in. and larger.

##### ⑤ Fittings, Weld Pads

0 = None

**Notes:** If required, enter code from pages 54 to 55. If none, enter "0".  
Weld pads available for 0.063 in. and larger.

##### ⑥ Lead Wire Termination

A = Standard male plug  
B = Standard female jack  
C = Standard plug with mating connector  
F = Miniature male plug  
G = Miniature female jack  
H = Miniature plug with mating connector  
T = Standard, 1 1/2 in. split leads  
U = 1 1/2 in. split leads with #8 spade lugs

##### ⑦ Sheath Material

A =	304/304L SS
F =	316/316L SS
C =	PFA coated over 304/304L SS (available on G, H and J diameter)
E =	316/316L SS with Teflon® encapsulation
Q =	Alloy 600 (Type K)

##### ⑧ ⑨ Sheath Length "L" (whole in.)

Available lengths: 01 to 99, for lengths over 99 inches contact factory.  
Maximum length for PFA coating is 48 in.

##### ⑩ Sheath Length "L" (fractional in.)

0 =	0
4 =	1/2

##### ⑪ Junction

	Grounded	Ungrounded	Exposed
Single	G	U	E
Dual*	H	W (isolated)	D (isolated)

\*Only available for 0.063 in. diameter and larger.

##### ⑫ Calibration

	E	J	K	T
Standard limits	E	J	K	T
Special limits	2	3	4	8

##### ⑬ ⑭ Lead Wire Length "E" (whole feet)

Available lengths: 01 to 30, for lengths over 30 contact factory

##### ⑮ Special Requirements

0 =	Standard 300°F (149°C)
H =	High temperature 1000°F (538°C) potting
M =	500°F (260°C)