


M23 powerfast Single Keyway Cordset Selection Matrix

			1 	1 	2 
			Straight Female	Straight Male	Straight Male
Pins	AWG	Current Rating	Single Keyway	Single Keyway	Single Keyway
6	14	20 Amps	CKM 64-078-*	CSM 64-078-*	CSSM 64-078-*
7	14	20 Amps	CKM 74-079-*	CSM 74-079-*	CSSM 74-079-*
9	3x14; 6x18	8 Amps (1-3,5,7,9), 20 Amps (4,6,8)	CKM 94-080-*	CSM 94-080-*	CSSM 94-080-*

M23 powerfast 3-Key Cordset Selection Matrix


			3 	4 	5 	6 
			Straight Female	Straight Male	Right Angle Female	Right Angle Male
Pins	AWG	Current Rating	3-Key	3-Key	3-Key	3-Key
6	12	30 Amps	CKM 622-059-*	CSSM 622-059-*	CKWM 622-059-*	CSSWM 622-059-*
8	4x12; 4x18	9 Amps (A-D), 30 Amps (1-4)	CKM 822-287-*	CSSM 822-287-*	CKWM 822-287-*	CSSWM 822-287-*

Pins	AWG	Current Rating	Shielded 3-Key	Shielded 3-Key	Shielded 3-Key	Shielded 3-Key
6	12	30 Amps	CKMS 622-286-*	CSSMS 622-286-*	CKWMS 622-286-*	CSSWMS 622-286-*
8	4x12; 4x18	9 Amps (A-D), 30 Amps (1-4)	CKMS 822-288-*	CSSMS 822-288-*	CKWMS 822-288-*	CSSWMS 822-288-*

M23 powerfast Single Keyway Receptacle Selection Matrix

Front Mount			7 	7 	8 	8 
			Female	Male	Female	Male
Pins	AWG	Current Rating	M20 Mount, Standard Thread	M20 Mounting, Standard Thread	M20 Mounting, Long Thread	M20 Mounting, Long Thread
6	14	20 Amps	CKF 64-6-*	CSF 64-6-*	CKFL 64-6-*	CSFL 64-6-*
7	14	20 Amps	CKF 74-7-*	CSF 74-7-*	CKFL 74-7-*	CSFL 74-7-*
9	3x14; 6x18	8 Amps (1-3,5,7,9), 20 Amps (4,6,8)	CKF 94-9-*	CSF 94-9-*	CKFL 94-9-*	CSFL 94-9-*

M23 powerfast 3-Key Receptacle Selection Matrix

Front Mount			9 	10 	11 
			Female	Male	Male
Pins	AWG	Current Rating	Flange Mount	Flange Mount	M20 Mounting Thread
6	12	30 Amps	CKFMF 622-6-*	CSFF 622-6-*	CSF 622-6-*
8	4x12; 4x18	9 Amps (A-D), 30 Amps (1-4)	CKFMF 822-8-*	CSFF 822-8-*	CSF 822-8-*



See pages 45-46 for dimensional drawings.

* Length in meters. Standard cable lengths are 2, 5 and 10 meters. Standard lead length is 0.5 meters. Consult factory for other lengths.





Note: Extension cables are available, please consult Part Number Key (page 42).

Standard coupling nut and housing material is nickel plated brass. Consult Part Number Key (page 42) for 316 stainless steel options.



M23 powerfast Single Keyway Cordset Dimensions



M23 powerfast 3-Key Cordset Dimensions




M23 powerfast Single Keyway Receptacle Dimensions



M23 powerfast 3-Key Receptacle Dimensions


9

CKFMF..




10

CSFF..



11

CSF..



M23 powerfast Single Key Cordset and Receptacle Pinouts

6-Pin		Pinouts	7-Pin		Pinouts
Female	Male		Female	Male	
		- WH - RD - GN - OG - BK - BU			- WH/BK - BK - WH - RD - OG - BU - GN

9-Pin		Pinouts
Female	Male	
		- RD - WH - WH/BK - BU - OG - BK - GN/BK - GN - RD/BK

M23 powerfast 3-Key Cordset and Receptacle Pinouts

6-Pin, 3-Key		Pinouts	8-Pin, 3-Key		Pinouts
Female	Male		Female	Male	
		- BU - RD - GN - BN - OG - YE			- BU - GN - WH - BK - OG - RD - WH/BK - RD/BK

M23 powerfast Single Keyway Cordset Specifications**Mechanical**

Mold material/Color:	PUR/Black
Contact carrier material:	Nylon or PBT
Coupling nut material:	
Standard:	Nickel plated brass
Additional options:	316 stainless steel
Environmental Protection:	IEC IP67
Temperature Rating:	-40 to +105°C (-40 to +221°F)

Electrical

Contact material:	Brass with gold plating
Cable jacket material/Color:	PVC/Yellow
Ratings:	
Power:	20 Amps, 300 V
Signal:	8 Amps, 150 V

M23 powerfast 3-Key Cordset Specifications**Mechanical**

Mold material/Color:	PUR/Black
Contact carrier material:	Nylon or PBT
Coupling nut material:	
Standard:	Nickel plated brass
Environmental Protection:	IEC IP67
Temperature Rating:	-40 to +90°C (-40 to +194°F)

Electrical

Contact material:	Brass with gold plating
Cable jacket material/Color:	TC-ER PVC/Yellow
Ratings:	
Power:	30 Amps, 600 V
Signal:	9 Amps, 300 V

M23 powerfast Single Keyway Receptacle Specifications**Mechanical**

Contact carrier material:	Nylon or PBT
Housing material/Plating:	
Standard:	Nickel plated brass
Additional options:	316 stainless steel
Environmental Protection:	IEC IP67
Temperature Rating:	-30 to +90°C (-40 to +194°F)

Electrical

Contact material:	Brass with gold plating
Conductor insulation:	PVC
Ratings:	
Power:	20 Amps, 300 V
Signal:	8 Amps, 150 V

M23 powerfast 3-Key Receptacle Specifications**Mechanical**

Contact carrier material:	Nylon or PBT
Housing material/Plating:	
Standard:	Nickel plated brass
Environmental Protection:	IEC IP67
Temperature Rating:	-30 to +80°C (-40 to +176°F)

Electrical

Contact material:	Brass with gold plating
Conductor insulation:	PVC
Ratings:	
Power:	30 Amps, 600 V
Signal:	9 Amps, 300 V