

- NEMA 1, 3, 4, 6P
- IEC IP68 Protection
- 60 VAC/75 VDC, 2 A



Housing Style	Female Part Number	Male Part Number	Features	Pinout
FK .. 14.5/NPT	FK 8-* /14.5/NPT	FS 8-* /14.5/NPT	8x24 AWG, 105°C, mates with 8-pin cordsets, UL Recognized, CSA Approved	<p>Female</p> <p>Male</p>
	FK 8.6-* /14.5/NPT	FS 8.6-* /14.5/NPT	6x24 AWG, 105°C, mates with 8-pin cordsets, UL Recognized, CSA Approved	<p>Female</p> <p>Male</p>
FS .. 14.5/NPT	FK 10-* /14.5/NPT	FS 10-* /14.5/NPT	10x24 AWG, 105°C, mates with 10-pin cordsets	<p>Female</p> <p>Male</p>
	FK 12-* /14.5/NPT	FS 12-* /14.5/NPT	12x24 AWG, 105°C, mates with 12-pin cordsets	<p>Female</p> <p>Male</p>

\* Length in meters. Standard lead length is 0.5 Meters. Consult factory for other lengths.

Standard housing material is nickel plated brass "FS.."; "FSV.." indicates stainless steel.

To specify PVC jacketed cable, add "/S717" to the end of the part number.