

2 and 4-Wire Receptacles, Front Mount, 1/2-14 NPT Threads


- NEMA 1, 3, 4, 6P
- IEC IP68 Protection
- 250 V, 4 A



Housing Style	Female Part Number	Male Part Number	Features	Pinout	
FK .. 14.5/NPT Typical panel cutout is 22.5 mm.	FK 4.2-*/14.5/NPT	FS 4.2-*/14.5/NPT	2x22 AWG, 105°C, mates with 2-pin cordsets	1. N/C 2. N/C 3. BN 4. BU	
	FK 4.22-*/14.5/NPT	FS 4.22-*/14.5/NPT	2x22 AWG, 105°C, mates with 2-pin cordsets	1. BN 2. N/C 3. BU 4. N/C	
FS ..14.5/NPT Typical panel cutout is 22.5 mm.	FK 4.4-*/14.5/NPT	FS 4.4-*/14.5/NPT	4x22 AWG, 105°C, mates with 4-pin cordsets	1. BN 2. WH 3. BU 4. BK	
	FK 4.4-*/14.5/NPT/S613	FS 4.4-*/14.5/NPT/S613	4x18 AWG, 105°C, mates with 4-pin cordsets	1. BN 2. WH 3. BU 4. BK	

* Length in meters. Standard lead length is 0.5 Meters. Consult factory for other lengths.

Standard housing material is nickel plated brass "FS.."; "FSV.." indicates stainless steel.

To specify PVC jacketed cable, add "/S717" to the end of the part number.