

4, 5 and 6-Wire Cordsets, Standard Duty

- NEMA 1, 3, 4, 6P
- IEC IP67 Protection
- 250 V, 4 A



Connector Style	Female Part Number	Male Part Number	Features	Pinout
KB ..** WKB ..**	KB 4T-* WKB 4T-*	SB 4T-* WSB 4T-*	AWM PVC Yellow, 4x22 AWG, 105°C, 5.7 mm OD, Cable #RF50555-*M [†] <i>flexlife</i> ®, UL Listed, CSA Recognized	Female Male
	KB 4T-*/S90 WKB 4T-*/S90	SB 4T-*/S90 WSB 4T-*/S90	AWM TPU Yellow, 4x22 AWG, 105°C, 5.7 mm OD, Cable #RF50614-*M [†] Cut/Abrasion Immune, UL Listed, CSA Recognized	
	KB 4T-*/S105 WKB 4T-*/S105	SB 4T-*/S105 WSB 4T-*/S105	AWM PVC Yellow, 4x22 AWG, 105°C, 5.7 mm OD, Cable #RF50656-*M [†] Braided Copper Shield, UL Listed, CSA Recognized	
	KB 4T-*/S727 WKB 4T-*/S727	SB 4T-*/S727 WSB 4T-*/S727	AWM TPU Grey, 4x22 AWG, 90°C, 5.1 mm OD, Cable #RF50532-*M [†] Special Conductor Color Code, UL Listed, CSA Recognized	
SB ..**	KB 5T-* WKB 5T-*	SB 5T-* WSB 5T-*	AWM PVC Yellow, 5x22 AWG, 105°C, 5.7 mm OD, Cable #RF50556-*M [†] <i>flexlife</i> , UL Listed, CSA Recognized	Female Male
WSB ..**	KB 6T-* WKB 6T-*	SB 6T-* WSB 6T-*	AWM PVC Yellow, 6x22 AWG, 105°C, 6.2 mm OD, Cable #RF51003-*M [†] <i>flexlife</i>	Female Male

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.

** Standard coupling nut material is nickel plated brass "KB .."; "KKB .." indicates nylon and "KBV .." indicates stainless steel.

† See Section N for **reelfast**® cable information.